

Features

- Best Value cost for blockout display
- Vibrantly and consistent printing quality
- Printable on both sides with uniform printing quality
- Super strong & durable polyester base fabric
- Best suited for indoor applications or outdoors when banner opacity is required

Applications



Technical Data Sheet

Item Code		FBCBFX680	Test Method
Base Fabric		1000D*1000D 18*18	DIN EN ISO2060
Weight (GSM)		680	DIN EN ISO2286-2
Tensile Strength	Warp (N/5cm)	2200	ISO527/3:1995
	Weft (N/5cm)	2100	ISO527/3:1995
Tear Strength	Warp (N/5cm)	280	ISO4674/1:2003
	Weft (N/5cm)	250	ISO4674/1:2003
Adhesion Strength		N/A	DIN53357:1982
Temperature		-30°C/+70°C	ISO13934-1:1999
RF Weldable (Heat Sealable)		YES	DIN53354
Flame Retardant		B1/M1/M2/NFPA701	

Information contained in this document is based on our general experience and is given in good faith. But we are unable to accept responsibility in respect to factors which are outside our knowledge or control.

Ink Printability

SOLVENT	ECO-SOLVENT	UV	LATEX	SCREEN PRINTING
■	■	■	■	■



Add: Room 912, No.3 Building, Shangdong Business Center, Haizhou District,
Haining, Zhejiang, China
Tel: +86-573-80776996 Fax: +86-573-80776998
Mob/Skype/Wechat/WhatsApp: +86-15858322153
<mailto:contact@hncomax.com> <https://www.hncomax.com>

